

# TECHNICAL DATA SHEET

According to Good Manufacturing Practice (CGMP) standards

GRADE: MNW045047H-SGP3  
DESCRIPTION: CELLULOSE NITRATE (MIXED ESTERS) MEMBRANE FILTERS. GRIDDED. 3 mm PINK HYDROPHOBIC EDGE  
DATE: MARCH 2016

This document is to verify that the designated product has been manufactured in conformance with applicable Current Good Manufacturing Practice (cGMP) standards.

The quality control data given in this document represent the quality of the released lot. These values are the basis for the official release of this material. The Quality Department for quality control of filters has measured the values and assures that they are within the limits that are established in the current specification for this material. The values stated do not represent any internal or external specification for this particular material. This product has passed external-house tests and thus meets Chmlab Group stringent quality control standards. The following is checked on a regular basis:

## Membrane Filter Characterization

PACKAGING: Boxes of 100 units  
FORMAT: Circles Ø 47 mm

### TECHNICAL SPECIFICATIONS:

Membrane.....Cellulose Nitrate (Ester)  
Pore size.....0.45 µm  
Membrane Color | Grid Color.....white | black  
Membrane wettability .....Hydrophilic  
Edge size .....3 mm  
Edge color .....Pink  
Edge wettability .....Hydrophobic  
Bubble point minimum value, wetted with water.....2.5 bar  
Flow rate for water.....69 ml/min [cm<sup>2</sup> at 1 bar (100kPa) differential pressure]  
Thickness .....90-140 µm  
Sterilization.....By autoclaving at 121 °C, with γ-radiation 25 KGray or EO  
Thermal Stability.....Max. 130°C  
Extractables.....With water less than 1%

## Other Specifications

<b>Properties</b>	They are ready-to use membranes and save preparatory time. Filter identification and lot number are printed on the box or on each individual enveloped Hydrophilic membrane. Hydrophobic edge of 3 mm Very uniform pore structure which ensures homogeneous distribution of particles retained on the filter surface Autoclavable Very high flow rate.
<b>Applications</b>	Clarification and sterilisation of aqueous solutions Microbiological analysis and particle counting Particle size analysis Pre-filtration and clarification of samples prior to further analysis Removal of particles in suspensions to determinate the degree of impurity