

SHIFT FILTRATION

TECHNICAL DATA SHEET According to Good Manufacturing Practice (CGMP) standards

V3.0



This document is to verify that the designated product has been manufactured in conformance with applicable Current Good Manufacturing Practice (cGMP) standards.

The quality control data given in this document represent the quality of the released lot. These values are the basis for the official release of this material. The Quality Department for quality control of filters has measured the values and assures that they are within the limits that are established in the current specification for this material. The values stated do not represent any internal or external specification for this particular material. This product has passed external-house tests and thus meets Chmlab Group stringent quality control standards. The following is checked on a regular basis:

Membrane Filter Characterization

_	PACKAGING: FORMAT:	Boxes of Circles (Ø mm):	100 units 25, 47	
	TECHNICAL SPECIFICATIONS:			
	Membrane			Polycarbonate
	Pore size			0.2 µm
	Wettability			Hydrophilic
	Bubble point mini	mum value, wette	ed with water	20 psi
	Flow rate for wate	er		10 ml/min [cm ² at 1 bar (100kPa) differential pressure]
	Sterilization			By autoclaving at 121 °C, with 🛽 -radiation 25 KGray or EO
	Extractables			Low extractables

Other Specifications

Properties	Made of high grade polycarbonate film Hydrophilic membrane High transluency High flow rate A very smooth and shiny surface on both sides facilitates easy sample examination Low extractables Low protein binding
Applications	Particulate analysis Epifluorescene microscopy Fluid clarification Cytology Biological test, cell biology and cell cultures Removal of red blood cells from plasma Water microbiology (analysis for Legionella in drinking water) Environmental analysis (detection of AOX in water)
Chemicalcompatibility	See chemical compatibility table on page 114 of our general catalogue http://www.chmlab.com/en/pdf/CHMLABcatalogue.pdf

www.chmlab.com